



# ANALOG BULLET CAMERA Outdoor

## Features

- DSP (Digital Signal Process)
- H.264,MJPEG,MPEG4 Video Compression
- Full Dual compressed Video stream
- Day & Night capable ( IR )
- User ID & Password ( Multi Level )
- HTTPS (SSL/TSL) Encrypted Data Transmission
- DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, NTP, QoS, RSTP, RTCP, RTP, RTSP, SMTP, SNMP,TCP/IP, UDP, UPnP supported protocols
- Remote configuration
- Web based tool
- Over network Remote System Update
- PC application client (with channel recording)
- Web Client Viewer through HTTP system configuration
- English Language display on the screen
- ON VIF Support
- Static and Dynamic IP Support, IPv6 readily available
- Compatible drivers and software included
- Iris Control
- 1 year warranty

## Specification

Model	HT-AB-H
Camera and Material	Bullet Camera with Aluminum Housing (IK10 rating ) ( Vandal Resistant )
Mounting bracket	Pole Mounted / Ceiling Mounted
Vari Focal Lens Type	√
CMOS Image Sensor	√
Camera Image Sensing	1Mega Pixels
Maximum Resolution	HD (1280 x 720 ) ( in Pixels)
Digital Zoom	10x
Frame Rate Per Second	25, 30 and 50
Minimum Illumination	0.01 lux

Image Sensor Size	1/3 inch (CMOS)
IR Range	30 mtrs (98 ft.)
Focal Length	2.8 - 12 (mm)
Manual Focus	√
Electronic Shutter Speed	1/3 to 1/30000 sec.
WDR	80 db
Signal to noise ratio	60 db
Auto Exposure	Electronic Level Control
White Balance	Indoor/Outdoor/Manual Selectable
Auto Gain Control	(On/Off / selectable)
Presets	255
Group Touring	9
Privacy Zones	√
No. of Privacy Zones	8
Simultaneous Connections	50
Ingress Protection	IP 66
Weight & Dimension	300 gram & 70 x 66 x 58 ( mm x mm x mm )
Power Input	12 V DC
Power Intake	5 Watt
Power Supply	230 V (+/- 10 %), 50 Hz
Operating Temperature	-10 to +50 deg C
Relative Humidity	95 Non Condensing (%)