



ANALOG DOME CAMERA Fixed Type Indoor

Features

- DSP (Digital Signal Process)
- H.264, MJPEG, MPEG4 Video Compression
- Full Dual compressed Video stream
- Day & Night capable (IR)
- User ID & Password (Multi Level)
- HTTPS (SSL/TSL) Encrypted Data Transmission
- Remote configuration
- Web based tool
- Remote System Update Over Network
- PC application client (With channel recording)
- Web Client Viewer through HTTP system configuration
- English Language display on the screen
- ON VIF and Audio Support
- Static, Dynamic IP Support with IP Address filtering
- SD Card Provision
- Compatible drivers and software included
- Iris Control
- 1 year warranty

Specification

Model	HT-ADF-I
Material	Plastic
Mounting bracket	Ceiling Mounted
Fixed Lens	$\sqrt{}$
CMOS Image Sensor	$\sqrt{}$
Camera Image Sensing	1Mega Pixel
Maximum Resolution	HD (1280 x 720) (in Pixels)
Frame Rate Per Second	25
Minimum Illumination	0.01 lux
Image Sensor Size	1/3 inch (CMOS)
IR Range	30 mtrs (98 ft.)
Focal Length	3.6 (in mm)

Electronic Shutter	1/50 to 1/30000 sec.
Speed	,
WDR / DWDR	80 db
Signal to noise ratio	60 db
Auto Exposure	Electronic Level Control
Manual Selectable	With Indoor & Outdoor Selectable
White Balance	
Auto Gain Control	(On/Off / selectable)
Presets	255
Group Touring	9
Privacy Zones	$\sqrt{}$
No. of Privacy Zones	24
Simultaneous	10
Connections	
Ingress Protection	IP 66
Weight & Dimension	200 gram & 85 X 69 (in mm x mm x mm)
Power Input	12 V DC
Power Intake	2 Watt
Power Supply	230 V (+/- 10 %), 50 Hz
Operating Temperature	-10 to +50 deg C
Relative Humidity	95 Non Condensing (%)



Techno info@hugotechno.com http://hugotechno.com/