



ANALOG DOME CAMERA Fixed Type Outdoor

Features

- DSP (Digital Signal Process)
- H.264,MJPEG,MPEG4 Video Compression
- Day & Night capable (IR)
- User ID & Password (Multi level)
- HTTPS (SSL/TSL) Encrypted Data Transmission
- Remote configuration
- Web based tool
- Over network Remote System Update
- PC application client (With channel recording)
- Web Client Viewer through HTTP system configuration
- English Language display on the screen
- ON VIF
- Static, Dynamic IP Support with IP Address filtering
- Compatible drivers and software included
- Dual compressed Video stream
- Iris Control
- 1 year warranty

Specification

| Model | HT-ADF-O |
|-----------------------|--|
| Material | Aluminum Housing with IK10 rating to avoid vandalism |
| Mounting bracket | Wall Mounted |
| Fixed Lens Type | √ |
| CMOS Image Sensor | √ |
| Camera Image Sensing | 1Mega Pixels |
| Maximum Resolution | HD (1280 x 720) (in Pixels) |
| Frame Rate Per Second | 25 |
| Minimum Illumination | 0.01 lux |
| Image Sensor Size | 1/3 inch (CMOS) |
| IR Range | 30 mtrs (98 ft.) |
| Focal Length | 3.6 (in mm) |

| | |
|---------------------------------|--------------------------------|
| Electronic Shutter Speed | 1/50 to 1/30000 sec. |
| WDR / DWDR | 80 db |
| Signal to noise ratio | 60 db |
| Auto Exposure | Electronic Level Control |
| Manual Selectable White Balance | With Indoor/Outdoor Selectable |
| Auto Gain Control | (On/Off / selectable) |
| Presets | 255 |
| Group Touring | 9 |
| Privacy Zones | √ |
| No. of Privacy Zones | 8 |
| Ingress Protection | IP 66 |
| Weight & Dimensions | 200 gram & 85 x 69 (mm x mm) |
| Power Input | 12 V DC |
| Power Intake | 2 Watt |
| Power Supply | 230 V (+/- 10 %), 50 Hz |
| Operating Temperature | -10 to +50 deg C |
| Relative Humidity | 95 Non Condensing (%) |



Techno
info@hugotechno.com
<http://hugotechno.com/>