



IP PTZ CAMERA Outdoor

Features

- H.264,MJPEG Video Compression
- Full Dual compressed Video stream
- Alarm provision
- Pre/post alarm buffer provision
- Day & Night capable (IR)
- User ID & Password (Multi level)
- IP address filtering, IPv6 readily available
- HTTPS (SSL/TSL) Encrypted Data Transmission
- Remote configuration and status using web based tool
- Remote System Update Over Network
- PC application client (with channel recording)
- Web Client Viewer through HTTP system configuration
- English Language on the Screen
- Supports Audio
- Compatible drivers and software included
- 1 year warranty
- Iris Control

Specification

Model	HT-NP-36W-O
Housing and Material of Camera	Dome Camera Vandal resistant Aluminum material (IK10 Rating)
Mounting bracket	Pole Mounted
Lens Type	Motorized Vari Focal
Image Sensor Type	CMOS
Camera Image Sensing	1.3Mega Pixels
Maximum Resolution	HD (1280 X 720 Pixel)
Optical Zoom	Upto 35x
Digital Zoom	Upto 16x
Frame Rate Per Second	25
Minimum Illumination	0.01 lux
Image Sensor Size	1/3 inch (CMOS)

IR Range	Upto 120 (in mtrs)
Focal Length	5 - 50 (in mm)
Auto & Manual Focus	Available (with Zoom)
Audio Compression	G.711,G.726
Audio Streaming	Two Way
Audio Channels	a. 1 input port b. 1 output port
Alarm I/ O	a. 2 Alarm Digital Input b. 1 Alarm Relay Output
Electronic Shutter Speed	1/5-1/10000sec.
WDR	80 db
Signal to noise ratio	50-60 db
Pan Range	From 0 to 360
Pan Speed	320 (deg/sec.)
Tilt Range	0-90 deg. (below horizontal) 0-5 deg. (above horizontal)
Tilt Speed	120 deg. / sec.
Auto Exposure	Auto Level Control
White Balance	Indoor/Outdoor/Manual Selectable
Auto Gain Control	(On/Off / selectable)
Presets	100
Group Touring	9
Privacy Zones	Available
No. of Privacy Zones	24
SD Card Support	64 GB Onboard SD Card Support
Simultaneous Connections	5-10
Ingress Protection	IP 66
Weight & Dimensions	3.5 Kg. & 186 x 309 (in mm)
Power Input	24VAC, 3AMP & POE
Power Intake	15- 30 Watt
Power Supply	230 V (+/- 10 %), 50 Hz
Operating Temperature	-10 to +50 deg C
Relative Humidity	95 Non Condensing (%)



info@hugotechno.com
<http://hugotechno.com/>