



HD IP DOME CAMERA Indoor

Features

- DSP (Digital Signal Process)
- H.264,MJPEG,MPEG4 Video Compression
- Full Dual compressed Video stream
- Alarm provision
- Pre/post alarm buffer provision
- Day & Night capable (IR)
- User ID & Password (Multi Level)
- IP address filtering, IPv6 readily available
- HTTPS (SSL/TSL) Encrypted Data Transmission
- Remote configuration
- Web based tool
- Over network Remote System Update
- PC application client (With channel recording)
- Web Client Viewer through HTTP system configuration
- English Language display on the screen
- ON VIF Support
- RTP,HTTP,RTSP,TCP/IP Supported Protocols
- Static, Dynamic IP Support
- Supports Audio
- Compatible drivers and software included
- Iris Control
- 1 year warranty

Specification

Model	HT-NDV-I-HD
Material	Aluminum
Mounting bracket	Wall Mounted
Vari focal Lens	√
CMOS Image Sensor	√
Camera Image Sensing	1.3Mega Pixels
Maximum Resolution	Full HD (1920 x 1080) (in Pixels)
Frame Rate Per Second	25

Minimum Illumination	0.01 lux
Image Sensor Size	1/3 inch (CMOS)
IR Range	30 mtrs. (98 ft.)
Focal Length	2.8 - 12 (mm)
Manual Focus	√
Audio Compression	G.726,G.711
Full Duplex Audio Streaming	√
Audio Channels	a. 1 port for input b. 1 port for output
Alarm I/ O	a. 1 port for Alarm Digital Input b. 1 port for Alarm Relay Output
Electronic Shutter Speed	1/50 to 1/30000 sec.
WDR /DWDR	80 db
Signal to noise ratio	60 db
Auto Exposure	Electronic Level Control
Manual Selectable White Balance	With Indoor/Outdoor Selectable
Auto Gain Control	(On/Off / selectable)
Presets	255
Group Touring	9
Privacy Zones	√
No. of Privacy Zones	24
Simultaneous Connections	10
SD Card Memory	64 Gigabytes
Ingress Protection	IP 66
Weight & Dimensions	890 gram & 159.1 X 117.9 (mm x mm x mm)
Power Input	12 V DC
Power Intake	5 Watt
Power Supply	230 V (+/- 10 %), 50 Hz
Operating Temperature	-10 to +50 deg C
Relative Humidity	95 Non Condensing (%)



Techno
info@hugotechno.com
<http://hugotechno.com/>