



## IP DOME CAMERA

## Outdoor

## **Features**

- DSP (Digital Signal Process)
- Full Dual compressed Video stream
- Alarm provision
- Pre/post alarm buffer provision
- Day & Night capable (IR)
- User & ID Password (Multi Level)
- IP address filtering, IPv6 readily available
- HTTPS (SSL/TSL) Encrypted Data Transmission
- Remote System Update Over Network
- PC application client (with channel recording)
- Web Client Viewer through HTTP system configuration
- English Display on the screen
- ON VIF Support
- RTP, HTTP, RTSP, TCP/IP Supported Protocols
- Static, Dynamic IP Support
- H.264, MJPEG, MPEG4 Video Compression
- Provision for Audio and External Microphone
- Compatible drivers and software included
- Iris Control
- Remote configuration and status using web based tool
- 1 year Warranty

## Specification

Model	HT-DV-O
Construction Material	Plastic
Mounting Set	Wall Mounted
Lens Type	Vari Focal
Image Sensor	CMOS
Camera Image Sensing	1.3MP
Maximum Resolution	Full HD (1920 x 1080) ( in Pixel)
Frame Rate Per Second	25
Minimum Illumination	0.01 lux
Image Sensor Size	1/3 inch (CMOS)

IR Range	30 (mtr) / 98 ft.
Focal Length	2.8 - 12 (mm)
Focus	Manual
Audio Compression	G.711,G.726
Audio Streaming	Full Duplex
Audio Channels	a. 1 input port
	b. 1 output port
Alarm I'/ O	a. 1 Alarm Digital Input
	b. 1 Alarm Relay Output
Electronic Shutter	1/50 to 1/30000 sec.
Speed	
WDR / DWDR	80 db
Signal to noise ratio	60 db
Auto Exposure	Electronic Level Control
Manual White Balance	√ (Indoor & Outdoor also available )
Auto Gain Control	(On/Off / selectable )
Presets	255
Group Touring	9
Privacy Zones	Available
No. of Privacy Zones	24
Simultaneous	10
Connections	
SD Card Memory	64 Gigabytes
Protection	IP 66
Weight & Dimension	890 gram & (159.1 X 117.9) ( mm x mm x mm)
Power Input	12 V DC
Power Intake	5 Watt
Power Supply	230 V (+/- 10 %), 50 Hz
Operating Temperature	-10 to +50 deg C
Relative Humidity	95 Non Condensing (%)



info@hugotechno.com http://hugotechno.com/