

LED Backlit 65 Inch Touch Screen



Hugo Techno presents 65" Full HD (1920 x 1080) LED touch screen. An elegant, appealing, smart and sleek structure with best-in-class reliability, stunning and crystal clear image quality. User-friendly and interactivity tools, duo System (Inbuilt Android, support OPS for Windows), Free Wi-Fi Hotspot Functionality gives you all plausible reasons to deploy it in your meeting, conference & classrooms.

Hugo Techno LED touch screens have multiple applications that will take your presentation & teaching to the next level.

The VDU 65HTG, an impressive interactive display that also offers you additional features.

- Screen Shot in Single Click
- Child Lock Setup to avoid misuse
- Lock USB port for Android
- USB Plug & Play in Android – Document, PDF, PPT, Video, Audio
- Eye Protection Writing Mode, Eye protection Brightness control mode as per light ambient
- Background Change for Android
- Scheduled Power On / Off
- Save Energy on Standby Time
- Wireless / Wired Printer Support

ANNOTATION FEATURE Annotate, edit, print, email, save, delete, copy, paste, color, choose pen, floating keyboard etc.

NETWORK CLASSROOM FEATURE Conduct sessions without any demographic limitations, through all types of media files.

ADDITIONAL FEATURE Word/PDF/ PPT /Excel Viewer, Intelligent Temperature control, Support Wi-Fi / LAN Printer, Input Resource Preview

Product Specifications:

Model	VDU 65HTG
Technology	LED Backlit IPS PANEL
Size of Display & Resolution	Diagonally 65 inches & Full HD (1920 x 1080)
Display Surface	3 mm thick toughened glass with 3H Hard Coating and Antiglare treatment of front polarizer (Haze 1% typ.)
Orientation	Landscape
Display Color	8 bit-16 million colours
Touch Technology	IR (Touch sensitive and pen driven)
No. of Touch	6 Touch capability
Brightness	500 cd/m ²
Aspect Ratio	16:9 / 16:10
Contrast Ratio	18000:1
Anti-Glare Panel Surface	Available
Viewing Angle (H/V)	178:178
Response Time	8 ms
Input / Output Ports	VGA IN x 1, VGA Out x 1, Video IN, Video Out, HDMI x 3, USB B Type for Touch x 1, SDIF, RS-232, YPbPr, USB port for Android x 2, LAN Port for Android x 1
Front Face Speakers	Inbuilt (10W x 2 RMS each)
Communication port	RS 232C, RJ45
Power supply	100-240V AC, 50 Hz
Power consumption	<220 Watts (Operational Mode); <0.5 Watts (Sleep Mode)
Operating Temperature and Humidity	0 deg. C - 40 deg. C and 20% to 80% RH
Supplied Accessories	AC Power cord, Stylus, User Manual, Remote control, Wall mount bracket, Cables and connectors