

# LED Backlit 65 Inch Touch Screen



Hugo Techno presents 65" Full HD (1920 x 1080) LED touch screen. An elegant, appealing, smart and sleek structure with best-in-class reliability, stunning and crystal clear image quality. User-friendly and interactivity tools, duo System (Inbuilt Android, support OPS for Windows), Free Wi-Fi Hotspot Functionality gives you all plausible reasons to deploy it in your meeting, conference & classrooms.

Hugo Techno LED touch screens have multiple applications that will take your presentation & teaching to the next level.

The VDU 65HTG-A, an impressive interactive display that also offers you additional features.

- Screen Shot in Single Click
- USB Plug & Play – Video, Audio
- Eye protection Brightness control mode as per light ambient
- Background Change
- Scheduled Power On / Off
- Save Energy on Standby Time

**ANNOTATION FEATURE** Annotate, edit, print, email, save, delete, copy, paste, color, choose pen, floating keyboard etc.

**NETWORK CLASSROOM FEATURE** Conduct sessions without any demographic limitations, through all types of media files.

**ADDITIONAL FEATURE** Word/PDF/ PPT /Excel Viewer, Intelligent Temperature control, Support Wi-Fi / LAN Printer, Input Resource Preview

### Product Specifications:

|   |  |
|---|--|
| <b>Model</b>                              | <b>VDU 65HTG-A</b>   |
| <b>Technology</b>                         | LED Backlit IPS PANEL  |
| <b>Size of Display &amp; Resolution</b>   | Diagonally 65 inches & Full HD (1920 x 1080)   |
| <b>Display Surface</b>                    | 3 mm thick toughened glass with 3H Hard Coating and Antiglare treatment of front polarizer (Haze 1% typ.)          |
| <b>Orientation</b>                        | Landscape  |
| <b>Display Color</b>                      | 8 bit-16 million colours   |
| <b>Touch Technology</b>                   | IR (Touch sensitive and pen driven)  |
| <b>No. of Touch</b>                       | 6 Touch capability   |
| <b>Brightness</b>                         | 500 cd/m <sup>2</sup>  |
| <b>Aspect Ratio</b>                       | 16:9 / 16:10   |
| <b>Contrast Ratio</b>                     | 18000:1  |
| <b>Anti-Glare Panel Surface</b>           | Available  |
| <b>Viewing Angle (H/V)</b>                | 178:178  |
| <b>Response Time</b>                      | 8 ms   |
| <b>Input / Output Ports</b>               | VGA IN x 1, VGA Out x 1, Video IN, Video Out, HDMI x 3, USB B Type for Touch x 1, SDIF, USB port x 2, LAN Port x 1 |
| <b>Speaker</b>                            | Inbuilt (10W x 2 RMS each)   |
| <b>Communication port</b>                 | RS 232C, RJ45  |
| <b>Power supply</b>                       | 100-240V AC, 50 Hz   |
| <b>Power consumption</b>                  | <220 Watts (Operational Mode); <0.5 Watts (Sleep Mode)   |
| <b>Operating Temperature and Humidity</b> | 0 deg. C - 40 deg. C and 20% to 80% RH   |
| <b>Supplied Accessories</b>               | AC Power cord, Stylus, User Manual, Remote control, Wall mount bracket, Cables and connectors                      |