

Smart Podium

With Steel Body, Wooden Top

Hugo Techno's Industrial grade Smart Podium is an integration of premier components that help to deliver flawless lectures & presentations. An opulent & well- formed external structure that has robust and premium body.



Podium Specification:

Model	HT-EL-301-SP
Type of podium	Free Standing, Processor based podium with polycarbonate body and Polymer coated CRCA steel sheet frame with screwless chassis and lockable drawers, sliding top with lock and key also acts as a protective cover, floor mounted, Soft wheels
CPU	Intel i5, 8th Gen, 4GB RAM, 1TB Hard Disk, Windows 10, MacAfee Anti Virus, Keyboard and Mouse
Display	
Type of Screen	Scratch resistant Vandal proof capacitive touch LED with antiglare protection glass overlay and motorized tilt control
Display Size & Resolution	21 inch & 1920 x 1080 resolution
Interactive Resolution	4000 Lpi (lines per inch)
Viewing Angles	170 degrees (H) ; 160 degrees (V)
Computer Interface	USB / HDMI/ DVI
Brightness	250 cd/m ²
Contrast	1000:1
Aspect Ratio	16:9
Response Time	8 ms
Viewing Angle	170 deg. (Horizontal); 160 deg. (Vertical)
Reading Accuracy	±0.5 mm (center)
Touch	Finger and Stylus (2mm diameter)
Interface	USB x 1, VGA/DVI/HDMI x 1
Touch Type	P-CAP and Electromagnetic Touch
Tracking Speed	200 points/ sec
Pen Pressure Sensitivity	1024 Levels
Audio (Built In)	
Microphones	1 handheld microphone, 1 lapel microphone with receiver (range- 10 metres)
Gooseneck Microphone	Gooseneck microphone (with XLR output) with the length of 21.5cm and LED indicator to depict On/Off status. It comes with a dedicated button to turn the microphone On and Off. The microphone is permanently polarized condenser microphone. It is highly directional featuring hypercardioid/lobar directivity. It comes with phantom power.
Amplifier	500W
Speaker	100W x 4
Central Controller	
Ports (Front)	VGA, HDMI, USB3.0 x 2, Audio IN
Ports (Rear)	USB 3.0 x 2, VGA Input x 2, VGA Output x 2, RCA Audio IN x 1, RCA Audio Output x 2, HDMI Input x 2, HDMI Output x 2, Programming Port
Wireless LAN Card	Buttons on front Panel of Controller
Buttons on front Panel of Controller	Push buttons to control volume up & down, volume mute to switch sources of HDMI visual presenter, VGA visual presenter, HDMI laptop, PC HDMI, VGA laptop, VGA PC & Controller Power On/Off, Display Power On and Power Off
Built in HDMI Repeater	HDMI Output port support 15mtr HDMI cable
Controller Resolution Output	4K (3840 x 2160)
Power	5V DC (Suitable Adaptor with controller)
Other information	
Power	180 -240V, 50Hz, AC Supply