

hugoTECHNO

Omni Directional Microphones and Speakers



Product Specifications:

Frequency Range	150Hz ~7.5kHz
Type	6 Element Array, Omni directional
Sound Channel	1.0
Output Power	1 × 10W
Maximum Sound Pressure Level	85 dB SPL@0.5m,1kHz
Signal to Noise Ratio	≥85dB
Voice Pickup Range	5m
Frequency Range	150Hz~16kHz
USB TypeC	1(Audio IN/OUT+Charge 5V/2A)
Button	6
LED Indicator light	Microphone Mute/ Volume Up/ Down/ Bluetooth/ Calling
Distortion	≤1% @1W,1kHz
AUX 3.5mm	1(Audio IN/OUT)
Bluetooth	BT4.2+EDR
Continuous working time	8h
Battery capacity	7.4V/2200mAh
Operating Frequency	2.4GHz
USB dongle	Support audio input and output Compatible with Windows, Mac system
Operating Distance	10m
Dimension	120 mm × 35.2mm Diameter × Height
Packaging Dimension	225 mm × 158 mm × 50 mm L × W × H
Battery charging	Wired:5V/2A, Wireless:5W(optional)
Accessory	USB Type C Cable x 1, Audio Cable x 1, USB Bluetooth Dongle x 1
Operation Humidity	10%~90%RH
Storage Humidity	10%~90%RH
Storage Temperature	20~ 60 degree C
Operation Temperature	0~40 degreeC
Net Weight	390g



info@hugotechno.com
<http://hugotechno.com/>

Hugo Techno is a progressive company, trusted throughout the world because of our commitment to customer satisfaction, environmental conservation individuality and teamwork. We are confident of our collective skills and meet challenges with innovation and creative solutions.

Model: Live HT-HD1