

# hugoTECHNO

8 Channel Network Video Recorder



## Product Specifications:

<b>Video Input</b>	8 Channel, IP
<b>Audio Output</b>	1xRCA
<b>Bandwidth</b>	Incoming : 50Mbps, Outgoing : 40Mbps
<b>HDMI &amp; VGA Output</b>	HDMI Resolution - 1: 2560×1440, 1920×1080, 1280×720, 800×600, 1024×768, 1366×768, 1440×900, 1280×800, VGA Resolution - 1: 1920×1080, 1440×900, 1366×768, 1280×800, 1280×720, 1024×768, 800×600
<b>Screen Split</b>	1/3/4/5/6/7/8/9
<b>Sample Rate</b>	8KHz/16KHz
<b>Synchronous Playback</b>	1x6MP, 1x5MP, 1x4MP, 1x3MP, 3x1080P, 4x720P
<b>Mode Search</b>	Time /Date, Alarm, MD and Exact Search
<b>Playback Function</b>	Playback Zoom , General Playback- Play, Pause, Stop, Rewind, Fast play, Slow Play, EventPlayback, Picture Playback
<b>Processor</b>	Quad-Core Processor (Main)
<b>Operating System</b>	Embedded LINUX
<b>Throughput</b>	90Mbps (Total)
<b>Recording Resolution</b>	6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF
<b>Recording Stream</b>	Single Stream Supported
<b>Video Compression</b>	H.265+, H.265, H.264
<b>Audio Compression</b>	Camera audio compression will synchronize
<b>Backup</b>	Video backup, Image Backup
<b>Trigger Events</b>	Recording, PTZ Setup, Sequence Interval, Buzzer and Screen Tips.
<b>Abnormal Warning</b>	Network Disconnect, Disk Full, Record Failed, Disk Error, No Disk.
<b>Video Content Analytics</b>	VCA detection alarm is supported
<b>Recording Type</b>	Continuous, Event (Motion Detection, Alarm, VCA, Smart Analysis)
<b>USB Interface</b>	USB 2.0 x 2
<b>SATA</b>	1 SATA Interface for 1 HDDs
<b>Maximum Capacity</b>	Up to 10TB capacity for each HDD
<b>Onvif</b>	Supported
<b>Network Interface</b>	1xRJ45 10/100Mbps
<b>IP Support</b>	Static, Dynamic
<b>Network Protocol</b>	TCP/IP, ICMP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, IGMP, QoS, IPV4, IPV6, Multicast, ARP, UDP, Telnet, RTMP
<b>AES Encryption</b>	AES128 Supported
<b>Multi Level User ID/ Password</b>	Supported
<b>Web Viewer</b>	IE, Chrome, Firefox, Safari
<b>Management Software</b>	Available
<b>Mobile Application</b>	Available
<b>User/Host</b>	32
<b>Power Supply</b>	DC-12V 3.33A
<b>Power Consumption</b>	≤10W(Without HDD)
<b>Operating Temperature</b>	-10°C~55°C, Less than 90% RH
<b>Rack Mountable Chassis</b>	1U Standard
<b>Dimensions</b>	44mmX255mmX231mm
<b>Weight</b>	0.8Kg
<b>Web Viewer</b>	IE, Chrome, Firefox, Safari



info@hugotechno.com  
<http://hugotechno.com/>

Hugo Techno is a progressive company, trusted throughout the world because of our commitment to customer satisfaction, environmental conservation individuality and teamwork. We are confident of our collective skills and meet challenges with innovation and creative solutions.

Model: HTR-BS208