hugoTechno Short Throw Projector





Specifications

Short Throw
4000 ANSI Lumens
1280 x 800
VGA 640 x 480 to Full HD 1920 x 1080
0.8x - 2.0x
One Chip DLP
UHP Lamp
1.07 Billion Colors
22000:1
0.49
0.63m-3.17m (87" @0.92m)
110% (+/-5%)
F=2.6, f=6.9mm
60"-300"
Horizontal (± 26°) & Vertical (± 40°)
30dB in Normal Mode, 27dB in Eco. Mode
USB Type A (power) x 1, USB type B mini x 1, RJ45 x 1, RS232 x1
HDMI x 2, Computer in/VGA x 2, Composite video x 1, Audio In x 1
VGA out x 1, Audio Out x 1
480i, 480p, 576i, 576p, 720p, 1080i, 1080p
8000 Hrs in Normal Mode, 10000 Hours in Economy Mode
10 Watts rms to deliver full range sound

Input Power Supply	All Compatible power cable & connector
Video Compatibility	NTSC, PAL, SECAM
Power Consumption	Normal: 260W, Standby: <0.5W
Remote	Full function remote control
Accessories	All device driver and cables for connecting with computer
Power Supply Voltage	100-240V+/- 10%, 50/60Hz (AC in)
Operating Temperature	0° C to 40° C, 0-90% RH
Packing Dimensions (WxDxH)	Adjustment Foot 292x236x115mm
Packing Dimensions	365 x 300 x 188mm
Special Features	4 corner adjustment, Auto Power On/ Off, Sleep timer, Power Saving mode, Password Protection, 3D Blu-ray, 3D ready, Keypad Lock



Hugo Techno info@hugotechno.com http://hugotechno.com/