

Web Cam



Product Specifications

Model	HT-DCFHD
Sensor	1/2.7", CMOS, Effective Pixel: 2.07M
Effective Pixel	2 MP
Field of View	78 degree
Autofocus	Support
Sliding Cover	Sliding cover available to protect camera lens when not in use.
Minimal Illumination	10 Lux
Camera bracket	bracket with damper
Backlight Compensation	Support
White Balance	Auto
Scanning Mode	Progressive
Digital Noise Reduction	2D&3D Digital Noise Reduction
Video System	1080P@30fps/25fps, 720p@30fps/25fps, 960x540p@30fps/25fps, 640x360p@30fps/25fps
Generic Specification	
Input Voltage	5V (USB power supply)
Current Consumption	Upto- 270mA
Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F)
Storage Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Power Consumption	upto 1.5W
USB Interface	1xUSB 2.0
Operational Requirement	
Resolution	Support 1080P Full HD Super Wide Angle, Support 1080 HD, can support 1080@30fps/25fps output, downward compatible with 720P, etc. Wide angel field of view. horizontal field of view can be 78°
Video Output	support USB 2.0, Full-featured USB 2.0 interface, power, video and audio all in one.
Built in Microphone	available Built-in microphone array to pick up sound equally from all directions. Unique noise reduction algorithm to accurately present your voice.
Low Light	support Features star-level CMOS sensor and 2D/3D noise reduction algorithm, delivering ultra-high SNR for optimized noise reduction. With a high SNR of 55dB, the image is still clear and sharp even in the low light environment.
Operate System Supported	Windows® 7 (1080P and under only), Windows 8.1, Windows 10 or higher macOS™ 10.10 Google™ Chrome-book™ Version 29.0.1547.70 , Linux
Video Format	1080P@30fps/25fps, 720p@30fps/25fps, 960x540p@30fps/25fps, 640x360p@30fps/25fps from USB

info@hugotechno.com
<http://hugotechno.com/>