

hugoTECHNO

Best Quality Add on Products

Specifications:

| 15-Meter USB Booster Cable Type A male to Female | |
|--|---|
| Length | 15 M |
| Audio/Video Transmission speed | 100 Mbps |
| Connector Material | Silver Plated |
| Cable Material | Plastic + Copper+ PVC |
| Conductor Material | Copper |
| Type | USB Type A Male to USB Type-A Female port |
| Cable Diameter | 2.5 mm |

| 6-Port Audio Mixing Console | |
|-----------------------------|---|
| Phantom Power | +48V |
| I/O Ports | Stereo Bus x1, Mic x2 / Line Inputs x6 (mono x2 + stereo x2) , XLR balanced outputs |
| Sound effects | High-grade effects: SPX with 6 programs |
| Channel | 6-Channel Mixing Console |

| 1x4 HDMI Switcher | |
|-------------------|---------------------|
| HDMI Switcher | 1x Input, 4x Output |
| Bandwidth | 2.5 Gbps |
| HDMI & HDCP | Supported |
| Output Resolution | 1080p |
| Output Status | Led Indicator x4 |

| 4x1 Full HD video Mixing Switcher | |
|-----------------------------------|---|
| HDMI Switcher | 4x Input, 1x Output |
| Video Layout | 1,2,3,4 HDMI Input supported on single screen |
| Output Resolution | 1080p |
| Output Status | Led Indicator x4 |

| Full HD Wireless Presentation System with USB Dongle | |
|--|---------------------------|
| Frame Rate | 30 fps |
| Maximum Number of Simultaneous sources on Screen & Connections with the system | 2 Number |
| Output Resolution | 1080p |
| Wireless Standards | 802.11 a/b/g/n |
| Wireless Frequency | 2.4 Ghz. |
| Data Transfer Rate | 1000 mbps |
| Wireless Range | 15m |
| Wireless Security | WPA2-PSK/TKIP-AES |
| Interfaces | 1x HDMI, 1x USB, 1 x RJ45 |
| Medium of data transmission (From Computer/Laptop to system) | Through dongle |
| Essential Accessories | Available |

| HDMI Capture Card | |
|-------------------|---|
| I/O Ports | Input: HDMI x1, Output: HDMI x1, USB x1 |
| Bandwidth | 2.5 Gbps |
| HDMI & HDCP | Supported |
| Output Resolution | 1080p |
| USB Video Output | USB Capture |

| HDMI to RJ45 Transmitter | |
|--------------------------|---|
| Transmitter (Tx) | HDMI x1 (Input), HDBT x1 on RJ45 (Output) |
| Receiver (Rx) I/O | HDMI x1 (Output), HDBT x1 on RJ45 (Input) |
| HDMI & HDCP | Supported |
| Transmission Range | Up to 50 meter |
| Output Resolution | 1080p |

| Wireless Handheld Microphone | |
|------------------------------|---|
| Microphone | 2x Handheld |
| Receiver | Non-Diversity Dual Channel |
| Frequency | 40Hz-16kHz |
| Polar Pattern | Cardioid (Hand mic) |
| Output | Individual Channel: XLR, Mix out: ¼" Jack |
| Channels | 200 Selectable UHF Channels |
| Channel Control | Individual channel output with level control & mix output |
| Pairing | Through Infrared |
| Frequency Identification | Back light display |
| Mic Power Requirement | 2 x 1.5V AA |
| Receiver | 240V AC 50Hz |