

hugoTECHNO

250 - watt Audio Amplifier



Specifications:

| 250 - watt Audio Amplifier | HT-AW-30 |
|-------------------------------|---|
| Amplifier | Class D, 250 W |
| Channel Crosstalk Attenuation | $\geq 50\text{dB}$ |
| Output | MIX OUT: 1000mV / 470 Ω unbalanced RCA connector |
| Mic & Line Input | 4 & 2 |
| Mute Function | MIC 1 is prior to MIC2-4, AUX1-2 audio input; EMC is prior to all audio inputs |
| Tone | Bass: $\pm 10\text{dB}$ at 100Hz; Treble: $\pm 10\text{dB}$ at 10KHz |
| Frequency Response | 80Hz ~16KHz (+ 1dB, -3dB) |
| SNR | MIC1,2,3: 66dB; AUX1,2: 85dB |
| THD | $< 0.05\%$ (at 1KHz, 1/3 rated power) |
| Impedance | MIC input: 5mV / 600 Ω balanced; AUX1,2 input: 350mV / 10K Ω unbalanced RCA connection terminal |
| Heat Dissipation | Side-in and rear-out forced fan cooling; fan starts automatically when the device is turned on; infinitely variable speed |
| Power Supply | AC ~ 220V / 50Hz |
| Power Consumption | 300W |
| Protection | Overheat protection, overcurrent protection, short circuit protection |



info@hugotechno.com

<http://hugotechno.com/>

Hugo Techno is a progressive company, trusted throughout the world because of our commitment to customer satisfaction, environmental conservation individuality and teamwork. We are confident of our collective skills and meet challenges with innovation and creative solutions.

Model: HT-AW-30