

# hugoTECHNO

Wall mount Speakers  
(HT-WMS-500)



## Specifications:

|                                  |  |
|----------------------------------|--|
| <b>Model</b>                     | HT-WMS-500   |
| <b>Enclosure Material</b>        | Polypropylene Structural Foam                        |
| <b>Input Connectors</b>          | Spring-loaded terminals                              |
| <b>HF Driver</b>                 | 19 mm (0.75 in) polycarbonate dome tweeter           |
| <b>LF Driver</b>                 | 135 mm (5.25 in) low frequency driver                |
| <b>Crossover Frequency</b>       | 4.3 kHz  |
| <b>Transformer Taps</b>          | 10 W, 5 W (& 2.5W @ 70V)                             |
| <b>Nominal Impedance</b>         | 8 ohms (in 8Ω DIRECT mode, selectable on back panel) |
| <b>Directivity Index (DI)</b>    | 7.9 dB   |
| <b>Directivity Factor (Q)</b>    | 6.2  |
| <b>Nominal Coverage</b>          | 120°H x 120°V  |
| <b>Maximum SPL (1m)</b>          | 106 dB at 8 Ohm Direct setting; 96 dB at 10W setting |
| <b>Sensitivity</b>               | 86 dB SPL, 1W (2.83V) at 1m (3.3 ft)                 |
| <b>Power Capacity</b>            | 50 Watts   |
| <b>Frequency Response(±3 dB)</b> | 120 Hz – 16 kHz                                      |
| <b>Frequency Range (-10dB)</b>   | 85 Hz – 18 kHz                                       |
| <b>Speaker Type</b>              | 2 Way drivers  |



info@hugotechno.com  
<http://hugotechno.com/>

Hugo Techno is a progressive company, trusted throughout the world because of our commitment to customer satisfaction, environmental conservation individuality and teamwork. We are confident of our collective skills and meet challenges with innovation and creative solutions.

**Model: HT-WMS-500**