

hugoTECHNO

Dome Network Camera



hugo
TECHNO

Model: HTC-D2A

Specifications:

Model	HTC-D2A
Image Sensor	1/2.7 Progressive Scan CMOS
Effective pixels	2592x1944
Frame Per Second	20fps@2592 1944, 25fps@2592x1520,1920x1080, 1280x720
Video Compression	H.265+, H.265, H.264+, H.264
Image sensing capacity	5MP
IR Distance	30 Mtr
Minimum Illumination	Color: 0.001Lux@F1.6, B/W: 0Lux with IR on
Shutter Speed	Auto/Manual, 1s ~ 1/100000s
Event Trigger	IP Address Conflict, Motion Detection, Mask Alarm
Image Setting	Saturation, Sharpness, Image Rotation, Brightness, Contrast
Image Enhancement Function	AWB, AGC
Lens	2.7mm ~ 13.5mm with Focusing & Motorised Zoom Lens (Acceptance of ± 10%)
Optical & Digital Zoom	16x Digital Zoom
Adjustment Angle Axis	3
Iris	Fixed
Viewing Angle	Horizontal: 100.4°~26.8°
Bandwidth	32Kbps ~ 8192Kbps
Noise / Signal Ratio	>60dB
Automatic Gain Control	White Balance, Electronic Day & Night (ICR)
Ethernet	1*RJ45 10M/100M
Privacy Masking	up to 4 Areas, Rectangular
WDR	120dB Wide Dynamic range
Advance Features	AWB, IP Address Filtering, AGC , BLC, HLC, 2D DNR, 3D DNR
Protocol	DNS, DDNS, MULTICAST, IPV4, NTP, UDP, Telnet, TCP/IP, HTTP, FTP, DHCP
Video Analytics	Tripwire, Perimeter
ONVIF	S, T , G
Access	On Android, Windows Phone
Users	8 users at same time
Storage	up to 256GB Micro SD (On-Board)
Temperature	-40°C~65°C, < 95% RH
Power Parameters on Ethernet	(802.3af)/ DC12V±10% on PoE
Power Consumption	7.5W, 9W with IR on



info@hugotechno.com
<http://hugotechno.com/>