

hugoTECHNO

Full HD PTZ Hybrid Video Conferencing



Product Specification

Full HD PTZ Hybrid Video Conferencing	HTMeet4-F
Sensor	1/2.8" (CMOS Sensor)
Effective Pixels	2.07M
Scanning Mode	Progressive
Optical / Digital Zoom	5x / 10x
Camera Resolution	1080p 30fps, 1080p 60fps
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
Lens	F1.8 ~ F2.8, f3.5mm ~ 42.3mm
White Balance	Outdoor, One Push, Manual, Auto, Indoor
Camera Features Supported	Image Freeze, H & V Flip, Backlight Compensation
Number of Presets and accuracy	255, 0.1° and 10 pre-sets on remote control
Video Resolutions	1080p, 720p, 540p, 480p, 360p, 240p
Digital Noise Reduction	2D&3D Digital Noise Reduction
Video S/N	≥55dB
Field of View	80°
Video System	1080p/60, 1080p/50, 1080p/30, 1080p/25
Pan Range / Speed	-170° to +170° / 2.7° ~ 35° / sec
Tilt Range / Speed	-30° to +90° / 1.7° ~ 31° / sec
Audio Encoding	AAC audio encoding for better sound quality and smaller bandwidth
Low Light	High SNR of CMOS sensor even under low illumination conditions
Simultaneous Video Output	Support HDMI, USB3.0 and LAN interface-based Video output HD video at the same time
Remote Control	All parameters of the camera remotely controlled by the high-speed communications, handheld remote control
PoE Power Supply & Controlling	Support PoE power supply for control, Video and audio with network
Redundant Power Supply	DC 12V, USB 5V, PoE (802.3af)
Operate System Supported	Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android
Video Format 3.0	1080P@60fps, 1080P@30fps, (YUY2 / H.264 / MJPEG)
Interface	USB 3.0 Type-C x 1, HDMI x 1, RJ45 x 1, (10M/100M Ethernet Interface) (Simultaneous Video Output), 3.5mm Audio Line In x 1, RS232 In x 1, RS485 x 1
USB Video Communication Protocol	UVC 1.5



info@hugotechno.com
<http://hugotechno.com/>

Hugo Techno is a progressive company, trusted throughout the world because of our commitment to customer satisfaction, environmental conservation individuality and teamwork. We are confident of our collective skills and meet challenges with innovation and creative solutions.

Model: HTMeet4-F

Video	H.264/MJPEG
Audio on USB	Support
Frame Rate	50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps
Audio Bit Rate	AAC 96Kbps, 128Kbps, 256Kbps
Video Stream	Main Stream Resolution(1920x1080,1280x720,1024x576), Sub Stream Resolution (1280x720,720x576, 320x240
Video Bit Rate	328Kbps ~ 20480Kbps (Variable Rate & Fixed Rate)
Temperature	Operating: -10°C ~ 40°C; Storage: -40°C ~ 60°C
Power Jack	JEITA type (DC IN 12V)
Support protocols	TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast
Input Voltage	DC 12V, USB DC 5V, PoE (802.3af)
Current Consumption	12V - 1.0A(MAX) / 5V - 1.5A(MAX)
Power Consumption	12W (Max)
Accessories	IR remote control, USB cable, Power adaptor and cable, user manual



info@hugotechno.com
<http://hugotechno.com/>

Hugo Techno is a progressive company, trusted throughout the world because of our commitment to customer satisfaction, environmental conservation individuality and teamwork. We are confident of our collective skills and meet challenges with innovation and creative solutions.

Model: HTMeet4-F