
## hugoTECHNO Ceiling Tile Microphone





info@hugotechno.com http://hugotechno.com/

## **Specifications:**

| Ceiling Tile Microphone          | HT-400TM  |
|----------------------------------|---|
| Audio Pickup Range               | 10 Meter Radius   |
| Audio Pickup pattern             | 360° Omnidirectional  |
| Digital microphone array         | Built-in 80 MEMS microphone connected in arrays to form a Omnidirectional   |
| Effective Audio pickup area      | 100 Sq Meter  |
| Multi Zones                      | 12 Zones beamforming  |
| Sensitivity                      | -38dBV/Pa 94dB SPL@1kHz   |
| SNR                              | 63 dB   |
| Audio Algorithms                 | Provide Clear Audio with 3A algorithms (AEC, AGC & ANS)   |
| Audio Features                   | Intelligent background noise suppression, Howling suppression, adaptive switching of pickup beams, and Smart reverberation ensure clear, comfortable communication and clear sound. |
| Audio Modes requirement          | Provide local audio reinforcement, remote audio only for remote conferences, and hybrid audio modes   |
| Intelligent voice Pickup         | Support Adaptive blind beamforming technology with automatic speaker alignment and speech reinforcement, to prevent from interference and to keep speech clear                      |
| Cascade                          | Capability to cascade up to 8 Unit in Daisy-chain mode using Cat-6 Cable  |
| AI Based Audio Processing        | Detect moving presenter voice and amplify it for audio processing   |
| AI based Human voice recognition | Identify human voice using deep learning AI capability and minimized other sound or noise to ensure clear speech in wide area   |
| Interface                        | 2 x RJ45 PoE port   |
| Mounting option                  | Ceiling mount and VESA bracket  |



info@hugotechno.com http://hugotechno.com/