

hugoTECHNO

Ceiling Flush mount



Specifications:

Ceiling Speaker	HT-MHT-06
Power	30W
Sensitivity	87 dB (1kHz - 16 kHz)
Frequency Response	100 Hz – 20 kHz
SPL	101 dB (low-impedance, 108 dB peak), 101 dB (top 70V/100V tap)
Impedance	8 Ω
Frequency Range	74 Hz – 20 kHz (-10dB)
Network for crossovers	<ul style="list-style-type: none">• 12 dB/oct (2nd order) high pass to HF driver• 12 dB/oct (2nd order) low pass to LF driver
Drivers	<ul style="list-style-type: none">• HF Driver: 19 mm (3/4 in)• LF Driver: 100 mm (4 in)
Transformer Taps	25 W, 12.5 W, 6.3 W @ 70V or 100V (plus 3.2 W @ 70V only)
Conical Coverage Angle	120 degrees
Factor of directivity	7.6
Directivity Index	8.1 dB



info@hugotechno.com
<http://hugotechno.com/>

Hugo Techno is a progressive company, trusted throughout the world because of our commitment to customer satisfaction, environmental conservation individuality and teamwork. We are confident of our collective skills and meet challenges with innovation and creative solutions.

Model: HT-MHT-06