

hugoTECHNO

Smart Podium



hugo
TECHNO

info@hugotechno.com
<http://hugotechno.com/>

Hugo Techno is a progressive company, trusted throughout the world because of our commitment to customer satisfaction, environmental conservation individuality and teamwork. We are confident of our collective skills and meet challenges with innovation and creative solutions. *images are for illustration purposes only

Product Specifications:

Digital Podium	HTEL-10B
Digital Podium	A mobile, free-standing electronic podium with locking omnidirectional wheels, featuring a polycarbonate body with sliding top.
Display	HTD-AU2R
Display	Equipped with a highly responsive, integrated interactive panel. The adjustable mortised tilt and advanced anti-shake stabilization provide a seamless, sturdy, and flawless writing surface
Contrast Ratio	1200:1
Colours	16.7M
Display Size	LED 21 inch IPS Technology with active area of 476.064mm(H)x267.786mm(V)
Resolution	1920 x 1080 Full HD
Brightness	250 cd/m ² (typ)
Aspect Ratio	16:09
Response Time	5ms
Operational Hours	30000 Hours
Viewing Angles	170° horizontal, 170° vertical
Curvature	Flat
Colour Gamut	72%
Interactive Method	EMR & P-CAP technology
Touch Type	Pressure-sensitive, cordless, battery-free
Resolution	5080LPI
Pressure levels	8192 Levels
Tracking speed	266PPS
Touch Accuracy	±0.5mm(centre); ±1mm(edge)
Touch Response	First touch:30ms; Continuous touch:5ms
Touch Screen	Multi-touch Points
Control Buttons	Power, Menu, +/-, Auto
Connectivity	USB x 1, HDMI x 1, DVI x 1, VGA x 1
Pen Type	Battery Free EM Pen
Pen Control	Two Key and Pen tip Control
Interactive Method	Electromagnetic resonance method
Display Stand	support tilting and Table standing type
Power Supply	12V DC
Controller	
Ports on front Panel of Controller	Audio IN, VGA, HDMI, USB3.0x2
Ports of Controller	HDMI Inputx2, HDMI Outputx2, USB 3.0 X 2,VGA Input x 2, VGA Output x 2, RCA Audio IN X 1,RCA Audio Output x 2
HDMI Repeater (supports 15m)	Yes
Buttons	HDMI Source Switch, VGA Source Switch, Volume Management, Power management
Power	5 V DC



info@hugotechno.com
<http://hugotechno.com/>

Microphone	
Gooseneck Microphone	A 21.5-inch, phantom-powered gooseneck condenser microphone with XLR output. It features an ON/OFF switch with an LED status indicator and utilizes highly directional hyper-cardioid/lobar directivity to deliver clear audio without the need for batteries.
Wireless Microphone	Wireless Handheld & Lapel microphone with receiver
Power and other	
Sliding Trays	Available
Security	Secured authentication system combining RFID, password protection, and a physical key
Power Supply	180 -240V, 50Hz, AC Supply
Environmental	
Operating temperature	5 to 40°C
Operating humidity	20 to 80% RH
Logo	Provided with Acrylic logo
Mini PC	
Processor	Intel Core i5, 10th Gen
RAM	16 GB
SSD Storage	512 GB
Ports	USB x 4, HDMI x 1, LAN Port x 1
Keyboard & Mouse	Included (Wireless)
Operating System	Windows 10